



SKU: # EVO244

  
Medical Grade

  
Anti Fingerprint

  
Anti Bacterial

  
CDC Cleaning

  
Ingress Protection

  
Made in USA

## 24" Evolution Multi-Touch LED Touch Screen

### Touch Screen Performance (Evolution-Touch)

- Superior High-Performance Projected Capacitive (Unlimited Touch Activations)
- 10 Point Multi-Touch (Finger, Capacitive Stylus, Nitrile, Latex and Vinyl Gloves)
- USB HID compliant & Driver free with no calibration
- Ultra Fast Precision Touch Response
- Requires human intentional touch (HIT)
- Anti-Fingerprint Oleophobic nano-coating
- Anti-Glare Diffuses mirror-like reflection
- Noise Immunity (Advanced technology to eliminate wide band and narrow band interference)
- 3mm thick, sealed full glass display
- Windows 8 (Swipe Zone)
- Multiple monitor supported (W8)
- Touch operation is unaffected by surface contaminants



### Display Performance

- Medical "A" Grade LCD Panel/ 16:9
- Edge-to-Edge sealed 3mm glass surface
- Integrated Multi-Media Speakers
- Industrial Cooling
- America's Best Commercial Warranty 4 Years with advanced replacement
- Proprietary CFD Designed Ventilation
- Custom vent system to limit dust collection and prevent fluid intrusion
- (MTBF) 124,000 Hours
- HDMI (HDCP Compatible) input provides expanded connectivity with advanced technology
- VESA compliant
- Locking power supply connection
- Made in the USA

### Applications

- Mission Critical
- Industrial
- Nurse Stations
- ERP
- Retail

### Certifications

- 60601-1
- IPX2
- IP34



Designed and Manufactured by Tech Global, Inc. in Chicago, IL

# SPECIFICATIONS

---

## Touch Interface

Touch Response

Evolution-Touch (PCT/ Anti-Fingerprint/ Anti-Glare): USB/ HID Compliant

5ms

## Display

Viewable Image Size

24/7 Medical "A" Grade Display/ Edge-Lit LED LCD

24"/ 16:9

Mean Time Between Failure (MTBF)

124,000 Hours

Pixel Pitch

0.25mm

Pixels Per Inch

102 @ native resolution

Brightness

250 cd/m<sup>2</sup>

Contrast Ratio

3000:1

Viewing Angle

178° Vert., 178° Hor.

Response Time

LCD Rapid Response (25ms)

## Synchronization Range

Horizontal

31.5 kHz to 81.1 kHz (Analog/Digital)

Vertical

56 to 76 Hz

## Internal Speakers

Built-in multimedia speakers provide quality sound

## Input Signal

Video

ANALOG 0.7 Vp-p/75 Ohms

Sync

TTL Level (Positive/Negative)

Input Connectors

DisplayPort, HDMI and DVI

Native Resolution

1920 x 1080 HD @ 60 Hz

## Power Consumption

On

18W/ Power Savings Mode .35W/

Dimensions (WxHxD)

Net (with stand)

23.5 x 14.4 x 8.1 in.

Net (without stand)

23.5 x 14.4 x 1.64 in.

Net Weight (with stand)

17 lbs.

VESA Hole Configuration Specification

100 x 100mm

## Environmental Conditions

Operating Temperature

5-35C/41-95F

Operating Humidity

20-80%

Operating Altitude

2000m / 6562 ft.

Storage Temperature

-10-60C/14-140F

Storage Humidity

10-85%

Storage Altitude

12,192m/40,000 ft.

## Warranty

4 years parts and labor including backlight and touch components

