

**View In 360**  
Click To Experience Evolution



SKU: # EVO274MD



## 27" Evolution MD Multi-Touch LED Touch Screen

### Touch Screen Performance (Evolution-Touch)

- Superior High-Performance Projected Capacitive (Unlimited Touch Activations)
- 10 Point Multi-Touch (Finger, Capacitive Stylus, Nitrile, Latex and Vinyl Gloves)
- USB HID compliant & Driver free with no calibration
- Ultra Fast Precision Touch Response
- Requires human intentional touch (HIT)
- Anti-Fingerprint Oleophobic nano-coating
- Anti-Glare Diffuses mirror-like reflection
- Noise Immunity (Advanced technology to eliminate wide band and narrow band interference)
- 3mm thick, sealed full glass display
- Touch operation is unaffected by surface contaminants



### Applications

- Mission Critical
- Industrial
- Nurse Stations
- ERP
- Retail

### Certifications

- 60601-1
- IPX2
- IP34

### Display Performance

- Medical "A" Grade LCD Panel/ 16:9
- Edge-to-Edge sealed 3mm glass surface
- Integrated Multi-Media Speakers
- Industrial Cooling
- America's Best Commercial Warranty 4 Years with advanced replacement
- Proprietary CFD Designed Ventilation
- Custom vent system to limit dust collection and prevent fluid intrusion
- (MTBF) 124,000 Hours
- HDMI (HDCP Compatible) input provides expanded connectivity with advanced technology
- VESA compliant
- Locking power supply connection
- Made in the USA



Designed and Manufactured by Tech Global, Inc. in Chicago, IL

# SPECIFICATIONS

---

## Touch Interface

Touch Response

Evolution-Touch (PCT/ Anti-Fingerprint/ Anti-Glare): USB/ HID Compliant

5ms

## Display

Viewable Image Size

24/7 Medical "A" Grade Display/ Edge-Lit LED LCD

27"/ 16:9

Mean Time Between Failure (MTBF)

124,000 Hours

Pixel Pitch

0.25mm

Pixels Per Inch

102 @ native resolution

Brightness

250 cd/m<sup>2</sup>

Contrast Ratio

3000:1

Viewing Angle

178° Vert., 178° Hor.

Response Time

LCD Rapid Response (25ms)

## Synchronization Range

Horizontal

31.5 kHz to 81.1 kHz (Analog/Digital)

Vertical

56 to 76 Hz

## Internal Speakers

Audio

Built-in multimedia speakers provide quality sound

In (1)

## Input Signal

Video

ANALOG 0.7 Vp-p/75 Ohms

Sync

TTL Level (Positive/Negative)

Input Connectors

DisplayPort, HDMI and DVI

Native Resolution

1920 x 1080 HD @ 60 Hz

## Power Consumption

On

29W/ Power Savings Mode .6W/

Dimensions (WxHxD)

Net (with stand)

25.8 x 15.7 x 8.1 in.

Net (without stand)

25.8 x 15.7 x 1.7 in.

Net Weight (with stand)

24 lbs.

Net Weight (without stand)

20 lbs.

VESA Hole Configuration Specification

100 x 100mm/ 200 X 100mm

## Environmental Conditions

Operating Temperature

5-35C/41-95F

Operating Humidity

20-80%

Operating Altitude

2000m / 6562 ft.

Storage Temperature

-10-60C/14-140F

Storage Humidity

10-85%

Storage Altitude

12,192m/40,000 ft.


## Warranty

4 years parts and labor including backlight and touch components



TechGlobal





15.7  
13.3 (Active Area)

23.6 (Active Area)  
25.8

Inputs Speaker Vents

1.7

OSD Controls

VESA Pattern

200(mm)  
100(mm)  
100(mm)



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
TECH GLOBAL. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
TECH GLOBAL IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES

Title  
**Tech Global 27" Display**

DO NOT SCALE DRAWING WEIGHT: SHEET 1 OF 2





**OSD Controls**



**Inputs:** DC Power, Display Port, DVI, HDMI, Audio In, USB Type B\*  
(As Seen Left To Right)

\*Touch Model Only

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
TECH GLOBAL. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
TECH GLOBAL IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES

Title  
**Tech Global 27" Display**

DO NOT SCALE DRAWING    WEIGHT:    SHEET 2 OF 2

